MAPPYWOOL FL

Description

MAPPYWOOL FL is a mat for footstep noise insulation made of 100% pure virgin wool. MAPPYWOOL FL is coupled with a film of natural polythene, recyclable and fully compatible with the environment. It can have a thickness of about 5/8mm.

Applications

MAPPYWOOL FL is ideal when an ecofriendly and high performance mat for footstep noise insulation is needed. With MAPPYWOOL FL is possible to achieve an acoustic and thermal insulation of inter-floor slabs in harmony with nature, using a single natural panel.

Laying

Place MAPPYWOOL FL on top of the plant levelling layer and seal the ends with MAPPYTAPE TXT adhesive (page 98) taking care not to leave gaps; the film must be placed facing up. Use MAPPYWOOL STRIP (page 91) between the horizontal partition and the just-placed mat to build a completely floating slab; trim the band only after placing the coating on the floor.

MAPPYWOOL FL can be cut using a cutter.

"Nothing is created, nothing is lost, everything is transformed" ... use the wool to dress up your home with nature!



New building



	WOOL							
CONTRACTOR NO	Colour	• • • • • • • • • • • • • • • • • • •						
いたので、	Weight	~ 400 - 800 g/m²						
	Thermal Conductivity λ	~ 0.04 W/mK (ISO 8302/91)						
No. A	Footstep noise reduction	thick. 5mm ΔLw=21db * (EN ISO 140-8:1999, 717-2:2007) thick. 8mm ΔLw=25db **						
	Dynamic stifness	thick. 5mm S't=28 MN/m ³ S'=54 MN/m ³ (UNI EN 29052-1:1993) thick. 8mm S't = 21 MN/m ³ , S'= 33 MN/m ³						

* Tested with a 5cm, 100 kg/m² sand-cement screed without any deviation from the specifications in force ** Calculation with a 6 cm, 100 kg/m² sand-cement screed

Items

	Code	W. (mm)	Thick. (mm)	Lg. (mt)	Colour Dis.	U.M.	No./ Pack.	Pack.	Dim.Pack. (cm)	Qty./ Pallet	RTS	Minimum
400 gr/mq.	I02F00514000100	1400	5	100	0	ml	100 ml	S/P	diam.82 cm.	-		100 ml
800 gr/mq.	I04F00914000050	1400	9	50	0	ml	50 ml	S/P	diam.82 cm.	-		50 ml



MAPPYWOOL FL is a product of the new **"MAPPY NATURALE - GREEN BUILDING PRODUCTS"** line Request a brochure or ask for info at our Customer Service!



